

## **Configuration Locks for NCP Secure Entry Client**

Note that the ID is essential for setting/removing configuration locks. If the ID will be forgotten, there is no possibility to remove or change the locks again!

If configuration locks are active in NCP Secure Entry Client, the locked configurations can no longer be changed by the user. Locked configurations are hidden in the client screen for all profiles, but remain effective.

This is how configuration locks are activated:

- 1. Start *Configuration* in the client monitor and go to *Configuration Locks*.
- 2. The Configuration Locking window opens up (see figure).

onfigurati	on Locks			×
General	Profiles	Mobile Ne	twork	
Cred	entials fo	or (un)locki	ng the configuration	
<u>U</u> ser ID:			Administrator	
<u>P</u> assword: Co <u>n</u> firm Password:			•••••	
			•••••	
Conf	iguration	Rights		
	Eirewall	oass of Service ates itions tions Options or VPN Path Settings <u>B</u> ac	Finder kup	
			<u>H</u> elp <u>O</u> K	<u>C</u> ancel

- 3. Enter a user ID and password under *Credentials for (un)locking the configuration*.
- 4. Under *Configuration Rights*, uncheck all boxes for the configurations that you no longer want to be configured or displayed.
- 5. Under the tabs *Profiles* and *Mobile Network* you will find further options for activating locks.
- 6. When all required locks are set, click on *Ok*. The locks are now active.
- 7. To deactivate the locks, go to *Connection* in the Client Monitor and click *Unlock Parameter Locks*.
- 8. Enter the ID that you entered previously when locking the configurations. The configuration locks will then be removed.